



Wall mount series adopts high-quality lithium iron phosphate batteries, equipped with intelligent BMS battery management system, long cycle life, high safety performance, beautiful appearance, free combination and convenient installation. LCD display, visualization of battery operating data. Compatible with most solar inverters, providing efficient energy for photovoltaic off-grid households, commercial and other electrical equipment.

Model	4850		48100		48200	
Specification	48V50Ah	51.2V50Ah	48V100Ah	51.2V100Ah	48V200Ah	51.2V200Ah
Combination	15S1P	16S1P	15S1P	16S1P	15S1P	16S1P
Capacity	2.4KWh	2.56KWh	4.8KWh	5.12KWh	9.6KWh	10.24KWh
Standard discharge current	50A	50A	50A	50A	50A	50A
Max. discharge current	100A	100A	100A	100A	100A	100A
Working voltage range	40.5-54VDC	43.2-57.6VDC	40.5-54VDC	43.2-57.6VDC	40.5-54VDC	43.2-57.6VDC
Standard Voltage	48VDC	51.2VDC	48VDC	51.2VDC	48VDC	51.2VDC
Max. charging current	50A	50A	50A	50A	100A	100A
Max. charging voltage	54V	57.6V	54V	57.6V	54V	57.6V
Cycle	3000~6000cycles @DOD 80%/25°C/0.5C					
Working humidity	65±20%RH					
Operating temperature	-10~+50°C					
Working altitude	≤2500m					
Cooling method	Natural cooling					
Installation	Wall mount					
Protection level	IP20					
Max of parallel	15PCS					
Warranty	5~10 Years					
Communication	Default: RS485/RS232/CAN Optional: WiFi/4G/Bluetooth					
Certified	CE ROHS FCC UN38.3 MSDS					
Product Size	400*200*585mm		400*230*585mm		400*230*610mm	
Package Size	500*260*630mm		500*290*630mm		460*250*650mm	
Net weight	35kg	40kg	42kg	46kg	102kg	106kg
Gross weight	40kg	45kg	50kg	54kg	112kg	116kg

*Voltage, capacity, size/color customization, OEM/ODM services can be provided according to customer needs

Wall mount Energy Storage Lithium Battery

- WALL MOUNT
- MAX 15PCS
- COMMUNICATION
- OEM/ODM

- LOW VOLTAGE PROTECTION
- OVER VOLTAGE PROTECTION
- OVER CURRENT PROTECTION
- OVER TEMPERATURE PROTECTION
- BALANCED PROTECTION
- OVER DISCHARGE PROTECTION
- SHORT CIRCUIT PROTECTION